

NAME	Kiyonori Mase	TEMP	20 °C	ENGINE	GS15R	MUFFLER	39065	MANIFOLD	39065
DATA	2003. 12. 7	HUMIDITY	50 %	HEAD CLEARANCE	0.2 mm	FUEL TYPE	BP PEAK POWER		
TRACK	KYOSHO CIRCUIT	TRACTION	80 %	PLUG No.	GS	RADIO	FUTABA 3PK		

SHOCK OIL	300 350 (400) 450 500 550 600 700
SHOCK PISTON	Pure Kit
SPRING	VZ073-4016
SPRING ADJUSTER	4.5 mm
SHOCK POS	U(N) IN CENTER OUT - L(U) L
CASTER ANGLE	2 mm
CAMBER ANGLE	0G / (1G) 0 0.5 (1.0) 1.5 2.0
TOE ANGLE	OUT 1°
FRONT WIDTH	197 mm
REBOUND STOP	0 mm
STABILIZER BAR	For R (X)
ONEWAY / DIFF. 4 Bevel	
DIFF OIL	# 10,000
GROUND CLEARANCE	6 mm
Servo Saver	(10) 11 12

SPACER	CASTER	ANGLE
4mm	6°	
3mm	8°	
2mm	10°	
1mm	12°	
0mm	14°	

BUMP/REBOUND	TIRE	V30
	TIRE INNER	92906S
	ST D/R	%

SHOCK OIL	300 350 (400) 450 500 550 600 700
SHOCK PISTON	Pure Kit
SPRING	Pure Kit
SPRING ADJUSTER	2 mm
SHOCK POS	Upper: (In) - Center - Out Lower: U - L
Upper Arm POS	Inside: U - (L) Outside: (U) - L
CAMBER ANGLE	0G / (1G) 0 0.5 1.0 1.5 (2.0) 2.5 3.0
TOE ANGLE	One Side 4°
REAR WIDTH	200 mm
REBOUND STOP	5 mm
STABILIZER BAR	SILVER BLACK GOLD
DIFF	4 Bevel
DIFF OIL	# 5,000
TIRE TYPE	V30
TIRE SIZE	92906S
GROUND CLEARANCE	6 mm

GEAR	18T	CLUCH SHOE	UM210	BODY	ASTRA
GEAR	47T	CLUCH SPRING	92741	SIDE PULLEY	25 26 (27)

memo. GT-2 Class Qualify 12L 5' 03 (3rd) Final 34L 10' 07 (2nd)	Use Option Parts VZW005 ▪ 39641
--	---------------------------------------