

NAME	Kazuhiro Miyazaki	TEMP	20 °C	ENGINE	GS15R	MUFFLER	39068	MANIFOLD	Standard
DATA	2003. 12. 7	HUMIDITY	50 %	HEAD CLEARANCE	0.2 mm	FUEL TYPE	BP Peak Power		
TRACK	KYOSHO CIRCUIT	TRACTION	80 %	PLUG No.	GS	RADIO	Futaba 3PK		

SHOCK OIL	300 350 400 450 (500) 550 600 700
SHOCK PISTON	2-1.0
SPRING	VZ073-4016
SPRING ADJUSTER	約 6 mm
SHOCK POS	Upper (N) In - Center - Out Lower (U) - L
CASTER ANGLE	2 mm
CAMBER ANGLE	0G / (1G) 0 0.5 (1.0) 1.5 2.0
TOE ANGLE	Out 1°
FRONT WIDTH	197 mm
REBOUND STOP	0 mm
STABILIZER BAR	For R (⊖)
DIFF. 4 Bevel	
DIFF OIL	# 20,000
GROUND CLEARANCE	5.5 mm
Servo Saver	(10) 11 12

SPACER	CASTER	ANGLE
4mm	6°	
3mm	8°	
2mm	10°	
1mm	12°	
0mm	14°	

BUMP/REBOUND	TIRE	V30
	TIRE INNER	92013
	ST D/R	75 %

SHOCK OIL	300 350 400 450 (500) 550 600 700
SHOCK PISTON	2-1.0
SPRING	Standard
SPRING ADJUSTER	約 1 mm
SHOCK POS	Upper: (n) - Center - Out Lower: U - L
Upper Arm POS	Inside (U) - L Outside (U) - L
CAMBER ANGLE	0G / (1G) 0 0.5 1.0 1.5 (2.0) 2.5 3.0
TOE ANGLE	One Side 3°
REAR WIDTH	200 mm
REBOUND STOP	4 mm
STABILIZER BAR	SILVER (BLACK) GOLD
DIFF	4 Bevel
DIFF OIL	# 5,000
TIRE TYPE	V30
TIRE SIZE	92013
GROUND CLEARANCE	6 mm

GEAR	15/17	CLUCH SHOE	UM210	BODY	ASTRA
GEAR	43/41	CLUCH SPRING	92741	SIDE PULLEY	25 26 (27)

memo. GT-2 Class Qualify 17L 5' 01 (1st) Final 33L 10' 01 (3rd)	Use Option Parts VZW005 VZW006 VZW007B VZW014 VZ075
--	--