

NAME	Team KYOSHO	TEMP	°C	ENGINE	GXR-15	MUFFLER	92971
DATE		HUMIDITY	%	HEAD CLEARANCE	mm	FUEL TYPE	
TRACK		TRACTION	%	PLUG No.	GS	RADIO	

CASTER	ANGLE
2mm	8.5°
1mm	10.5°
0mm	12.5°

SERVO SAVER	⑨ 10
SERVO ANGLE	95%
UPPER ARM POSITION	⊙ ⊕ ⊖ ⊗ ⊘ ⊙
KNUCKLE ARM SPACER	0 mm
KNUCKLE ARM TYPE	① 1° 2°
DIFF () / ONE WAY	Ⓜ RIGID

SHOCK OIL	Ⓝ 300 350 400 450 500 550 600
SHOCK TYPE	Ⓝ / VZ075
DIAPHRAGM	Ⓝ
SHOCK PISTON	Ⓝ
SPRING	Ⓝ BLACK
SPRING ADJUSTER	3 mm
SHOCK POSITION	1 ② 3
CASTER ANGLE	1 mm
CAMBER ANGLE	L 0 0.5 ① 1.5 2 2.5 3 OG ① R 0 0.5 ① 1.5 2 2.5 3
TOE ANGLE	-1°
FRONT WIDTH	198 mm
UP STOP	- mm
DOWN STOP	0 mm
ANTIROLL BAR	有 ① VZ084S Ⓝ VZ084 ⊖ ⊗ ⊘ ⊙
TIRE TYPE & HARDNESS	キット標準
INNER FOAM	キット標準
WHEEL TYPE	キット標準
CHASSIS HEIGHT	6 mm

GEAR	TOTAL	GEAR	TOTAL	GEAR	TOTAL	GEAR	TOTAL	GEAR	TOTAL
15	61	8.13	15	60	8.00	15	59	7.87	20
16	61	7.63	16	60	7.50	16	59	7.38	21
17	61	7.18	17	60	7.06	17	59	6.94	22
									23
									56
									55
									54
									53
									52
									51
									50
									49
									48
									47
									46
									45
									44
									43
									42
									41
									40
									39
									38
									37
									36
									35
									34
									33
									32
									31
									30
									29
									28
									27
									26
									25
									24
									23
									22
									21
									20
									19
									18
									17
									16
									15
									14
									13
									12
									11
									10
									9
									8
									7
									6
									5
									4
									3
									2
									1

SHOCK OIL	Ⓝ 300 350 400 450 500 550 600
SHOCK TYPE	Ⓝ / VZ075
DIAPHRAGM	Ⓝ
SHOCK PISTON	Ⓝ
SPRING	Ⓝ BLACK
SPRING ADJUSTER	1.5 mm
SHOCK POS	1 2 ③ 4
WHEEL SPACER	Ⓝ 0mm / 2mm
UPPER ARM HEIGHT	0 mm ① IN/OUT
CAMBER ANGLE	L 0 0.5 1 ① 1.5 2 2.5 3 3.5 4 OG ① R 0 0.5 1 ① 1.5 2 2.5 3 3.5 4
TOE ANGLE	3°
REAR WIDTH	200 mm
DOWN STOP	4 mm
ANTIROLL BAR	Ⓝ 1.3/1.4
TIRE TYPE & HARDNESS	キット標準
INNER FOAM	キット標準
WHEEL TYPE	キット標準

FLYWHEEL	Ⓝ	PINION GEAR	① 15 16 17 / ② 21 22 23
CLUCH SHOE	Ⓝ UM210	SPUR GEAR	59 60 ① 61 / 55 ② 56
CLUTCH SPRING	Ⓝ	BRAKE	NORMAL 60 %
		REAR DIFF	キット標準グリス

CHASSIS HEIGHT	6 mm
LOWER ARM POSITION	⊙ ⊕ ⊖ ⊗ ⊘ ⊙
BODY	
WING HEIGHT	N mm

MEMO